



WATER TANK OUTLET "OPTIONAL"  
USCITA ACQUA SERB.ACC."OPZ."  
(D.W.T.)

ELECTR. CABLE INLET  
INGR. CAVI ELETT.

\* BASE FIXING HOLES POSITION

RANGE AMBIENT TEMPERATURE.  
LIMITI TEMPERATURA AMBIENTE 5°C 45°C

MAX WATER PRESSURE  
PRESSIONE MASSIMA ACQUA 6 BAR 30°C

REFRIGERANT: R407C

VICTAULIC CONNECTIONS: (DN100 / Ø4")  
CONNESSIONI VICTAULIC

WELDED CONNECT.: (114,3mm)  
CONNESSIONI A SALDARE

MODEL MODELLO	WATER CONNECTIONS ATTACCHI ACQUA (VICTAULIC CONNECTIONS) (WELDED CONNECT.)			WEIGHT PESO (KG)
	I.E.	O.E.	D.W.T.	
ICE310	4"	4"	4"	2900
ICE360	114,3	114,3	114,3	3100

REV. 03	General update	Material	Approval date	Sheet n° 1 of n° 1
Sostituisce disegno - Replaced drawing		N°prog.-Design N° 1024	02/12/2010 16.41.00	Approved by POLENTA
Modif/Request N°		Material	08/03/2004 0.00.00	Dis- Draftsman TESSARD
Denominazione - Denomination		Destinazione - Destination		REV. 03
OVERALL DIMENSIONS		BAA360INOA		
DIMEN. INGOMBRO ICE310-360 50/60Hz		HYPERCHILL		